

ORCA 19" Full IP66 Display

Full IP66 Industrial Touch Display

Features

- Full IP66 Stainless Steel Enclosure
- Full flat resistive Touch Display
- M12 Connectors

Display

| | |
|------------------|-----------------------------------|
| Size | 19" 5:4 |
| Touch Type | Full flat resistive touch panel |
| Resolution | 1280 x 1024 |
| Number of Colors | 16.7M colors (RGB 6-Bit + Hi FRC) |
| View Angle | 170 (H) / 160 (V) |
| Contrast Ratio | 1000:1 |
| Brightness | 350 cd/m ² |

Interface

| | |
|---------------|--|
| USB | 1x M12 8-Pin |
| Audio | 1x VGA input |
| Video | 1x HDMI input |
| Power input | DC 12 V |
| Power adapter | AC 90 ~ 264 V / 47 ~ 63 Hz / DC Output 12V |

Mechanics/ Environment

| | |
|---------------|--|
| IP | Full IP66 / Full IP69K |
| Dimensions | 458 x 386 x 64mm |
| Mounting | VESA Mount 100 |
| Temperature | Operating: -10° bis 55°C / Storage: -30° bis 70°C |
| Weight | 10kg |
| Certification | FCC / CE (EMC) / VCCI Class B (VGA port) / Class A (HDMI port) |

Front



Technical Layout

