



COMPACT 4G LTE
M2M ROUTER



Manage this device with
Digi Remote Manager

DIGI TRANSPORT WR11 XT

Secure 3G/4G/LTE cellular router for retail, kiosk and industrial control applications

Digi TransPort® WR11 XT delivers a cost-optimized 4G LTE connection to mission critical M2M applications around the world. These cellular routers are ideal for connecting:

- Building and process automation controllers
- Smart grid assets (meters, switches and controllers)
- IP cameras and access controllers
- Remote data loggers, flow meters and sensing equipment
- Telco infrastructure controllers
- ATMs, kiosks and service terminals



Digi TransPort WR11 XT provides a secure, reliable connection to industrial controllers, retail terminals and process automation equipment on third party sites or remote locations. This drop-in connectivity gives operators a way to reduce the cost of downtime and service calls and also increase revenue by bringing distributed sites online faster.

Gain critical insights into your deployed devices and manage your network with Digi Remote Manager® — the command center for your deployment. Digi Remote Manager (Digi RM) is a cloud-based solution that facilitates easy setup, mass configuration, maintenance and support for hundreds or even thousands of remote Digi devices.

BENEFITS:

- Global HSPA+ and 4G LTE support and certification
- Extremely resilient cellular connection through patented Digi SureLink®, VRRP+ protocol and dual SIM slots
- Enterprise routing features for security, logging and redundancy (e.g., stateful firewall, VPN, SNMP); no annual enterprise software license required
- Digi Remote Manager platform for easy setup, mass configuration and management
- Rugged aluminum enclosure, flanges and optional DIN rail clip for flexible mounting

APPLICATION EXAMPLE



RELATED PRODUCTS




Digi TransPort®
WR21



Digi TransPort®
WR31



Digi TransPort®
WR44 R



Accessories



Digi Remote
Manager®

SPECIFICATIONS

Digi TransPort® WR11 XT

CELLULAR

LTE - EMEA (M3)
 LTE Cat 1: 800(B20)/900(B8)/1800(B3)/2100(B1)/2600(B7)
 2G EDGE: 900/1800 MHz
 Transfer rate (max): 10 Mbps down, 5 Mbps up

LTE - EMEA/APAC (L7)
 LTE Cat 3: 800(B20)/1800(B3)/2600(B7)
 3G HSPA+: 900/2100 MHz
 2G Edge/GPRS: 850/900/1800/1900 MHz
 Transfer rate (max): 100 Mbps down, 50 Mbps up

LTE - UNITED STATES (M4)
 LTE Cat 1: 700(B12)/850(B5,B26)/AWS(B4)/1900(B2,B25)
 Transfer rate (max): 10 Mbps down, 5 Mbps up
 Approvals: Sprint (pending)

LTE - NORTH AMERICA (M6)
 LTE Cat 1: 700(B12,B13)/850(B5)/AWS(B4)/1900(B2)
 HSPA+: 850/1900 MHz
 Transfer rate (max): 10 Mbps down, 5 Mbps up
 Approvals: PTCRB, AT&T, Verizon, Telus (pending)

LTE - ANZ/LATAM (M9)
 LTE Cat 1: 700(B28)/850(B5)/900(B8)/1800(B3)/2100(B1)
 3G HSPA+: 850/900/2100 MHz
 Transfer rate (max): 10 Mbps down, 5 Mbps up

GLOBAL HSPA+ - (U9)
 3G HSPA+: 850/900/1700AWS/1900/2100 MHz
 2G EDGE/GPRS: 850/900/1800/1900 MHz
 Transfer rate (max): 21 Mbps down, 5.76 Mbps up
 Approvals: PTCRB

CONNECTORS
 (2) 50 Ω SMA (center pin: female); (1) connector for non-LTE models

SIM SLOTS
 (2) Mini-SIM (2FF)

SIM SECURITY
 Screw-down SIM cover

SOFTWARE & MANAGEMENT

REMOTE MANAGEMENT
 Digi Remote Manager® (cloud based); SNMP v1/v2c/v3 (user installed/managed)

LOCAL MANAGEMENT
 WebUI (HTTP/HTTPS); CLI (Telnet, SSH, SMS)

MANAGEMENT/TROUBLESHOOTING TOOLS
 FTP, SFTP, SCP; protocol analyzer with PCAP for Wireshark; event logging with Syslog and SMTP; NTP/SNTP

MEMORY
 20 MB RAM, 10 MB file space

ETHERNET

PORTS
 (1) RJ-45; 10/100 Mbps (auto-sensing)

PHYSICAL

DIMENSIONS (L X W X H)
 7.62 cm x 10.16 cm x 2.54 cm (3 in x 4 in x 1 in)

WEIGHT
 .22 kg (0.5 lb)

STATUS LEDS
 Power on, WWAN signal strength, WWAN service

ENCLOSURE
 Industrial (metal) / IP30

POWER REQUIREMENTS

POWER INPUT
 5 VDC, 15 W minimum power source required

POWER SUPPLY
 Must be used with a Digi approved power supply

POWER CONSUMPTION
 3.5 W typical (Idle); 10 W typical (Peak Tx/Rx)

ENVIRONMENTAL

OPERATING TEMPERATURE
 -30° C to 70° C (-22° F to 158° F) reduced cellular performance may occur above 60° C (140° F)

RELATIVE HUMIDITY
 5% to 95% (non-condensing)

APPROVALS

CELLULAR
 PTCRB

SAFETY
 UL 60950, CSA 22.2 No. 60950, EN60950

EMISSIONS/IMMUNITY
 CE, FCC Part 15 Class B, AS/NZS CISPR 22, EN55024, EN55022 Class B


WARRANTY

PRODUCT WARRANTY
 3-year*


*Standard 3-year warranty upgradeable to 5 years with purchase of a Digi Remote Manager Premier 5-year subscription applicable to the product purchased only at the time of product purchase and with product registration at that time in Digi Remote Manager.

PRODUCT IMAGES


DIGI TRANSPORT® WR11 XT - TOP



LEFT SIDE



RIGHT SIDE



ENTERPRISE SOFTWARE	DESCRIPTION
PROTOCOL SUPPORT	HTTP, HTTPS, FTP, SFTP, SSL, SMTP, SNMP (v1/v2c/v3), SSH, Telnet and CLI for web management; Remote management via Digi Remote Manager®; SMS management, protocol analyzer, ability to capture PCAP for use with Wireshark; DynDNS; Dynamic DNS client compatible with BIND9/No-IP/DynDNS
SECURITY/VPN	IP filtering, stateful inspection firewall with scripting, address and port translation; VPN: IPsec with IKEv1, IKEv2, NAT Traversal; SSL, SSLv2, SSLv3, FIPS 197, open VPN client and server; PPTP, L2TP;(5) VPN tunnels (not upgradable); Cryptology: SHA-1, MD5, RSA; Encryption: DES, 3DES and AES up to 256-bit (CBC mode for IPsec); Authentication: RADIUS, TACACS+, SCEP for X.509; certificates; Content filtering (via 3rd party); MAC address filtering; VLAN support
ROUTING/FAILOVER	IP pass-through; NAT, NAPT with IP port forwarding; Ethernet bridging; GRE; Multicast routing; Routing protocols: PPP, PPPoE, RIP (v1, v2) OSPF, SRI, BGP, iGMP routing (multicast); IP failover: VRRP, VRRP+TM; Automatic failover/ failback to second GSM network/standby APN
OTHER PROTOCOLS	DHCP; Dynamic DNS client compatible with BIND9/No-IP/DynDNS; QoS via TOS/DSCP/WRED

DIGI REMOTE MANAGER®



Digi Remote Manager is the technology platform that brings networks to the next level, allowing networks — and the people who manage them — to work smarter. With Digi Remote Manager you can transform a multitude of dispersed IoT devices into a dynamic, intelligent network. Now you can easily deploy, monitor and diagnose thousands of mission-critical devices from a single point of command — on your desktop, tablet or phone. All the while, its software-defined security diligently safeguards your entire Digi ecosystem.

Learn more at www.digi.com/digi-remote-manager

CAPABILITIES

- Activate, monitor and diagnose your mission-critical devices from a single point of command and control — on your desktop or mobile app
- Schedule key operations — including firmware updates and file management — on a single device or on a group of devices, keeping your network functionality up-to-date and maintaining compliance standards
- Manage edge devices out-of-band via console terminal access
- Keep tabs on device health and connectivity across device deployments of any size
- Create detailed reports and enable real-time alerts for specified conditions
- Integrate device data through open APIs to gain deeper insights and control with third-party applications
- Report and alert on performance statistics, including connection history, signal quality, latency, data usage and packet loss

INFRASTRUCTURE

- Hosted in a commercial-grade cloud server environment that meets SOC 1®, SOC 2® and SOC 3® standards
- Superior availability, operating to 99.9% or greater
- Open APIs available to support application development

SECURITY

- More than 175 security controls in place to protect your data
- Member of the Center for Internet Security® (CIS®)
- Enables compliance with security frameworks like ISO27002, HIPAA, NIST and more
- Earned Skyhigh's CloudTrust™ Program highest rating of Enterprise-Ready

PART NUMBERS	DIGI TRANSPORT® WR11 XT
WR11-M300-DE1-XB	Digi TransPort WR11 XT - 4G LTE EMEA/APAC, single Ethernet
WR11-M400-DE1-XB	Digi TransPort WR11 XT - 4G LTE Sprint, single Ethernet
WR11-M600-DE1-XB	Digi TransPort WR11 XT - 4G LTE North America, single Ethernet
WR11-M900-DE1-XB	Digi TransPort WR11 XT - 4G LTE APAC/LATAM, single Ethernet
WR11-L700-DE1-XB	Digi TransPort WR11 XT - 4G LTE EMEA/APAC, single Ethernet with 2G/3G fallback
WR11-U900-DE1-XB	Digi TransPort WR11 XT - HSPA+ Global, single Ethernet

PART NUMBERS	DESCRIPTION
76000926	Antenna - cellular, 3G/4G/LTE
76000954	Antenna base – SMA, 1m, RG174
76002074	Accessory kit - AC power, std temperature, EU plug
76002065	Accessory kit - DC power
76002062	Accessory kit - AC power, std temperature, US plug
76002063	Accessory kit - AC power, std temperature, intl plugs
76002064	Accessory kit - AC power, extd temperature, intl plugs
76000935	AC power supply - EU plug to 5 VDC - 2.5 mm locking barrel plug
76000965	AC power supply - extd temperature, universal plugs (US, EU, UK, AU) to 5 VDC - 2.5 mm locking barrel plug
76000934	AC power supply - US plug to 5 VDC - 2.5 mm locking barrel plug
76000976	DC power supply - converts 9-30VDC to 5 VDC - 2.5 mm locking barrel plug
76002021	AC power supply - std temperature, universal plugs (US, EU, UK, AU) to 5 VDC - 2.5 mm locking barrel plug
76000826	Cable - Ethernet, RJ-45 to RJ-45, 2 m
76000682	Mounting Bracket – DIN Rail
76000826	Cable - Ethernet, RJ45 to RJ45, 2m

*Sold separately, unless otherwise noted.

PART NUMBERS	DIGI REMOTE MANAGER®
DIGI-RM-STD-1YR	Digi Remote Manager Standard - 1-year subscription
DIGI-RM-PRM-1YR	Digi Remote Manager Premier - 1-year subscription
DIGI-RM-PRM-3YR	Digi Remote Manager Premier - 3-year subscription
DIGI-RM-PRM-5YR	Digi Remote Manager Premier - 5-year subscription

DIGI SERVICE AND SUPPORT / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

© 1996-2020 Digi International Inc. All rights reserved.
All trademarks are the property of their respective owners.

91004202
C1/920

DIGI INTERNATIONAL WORLDWIDE HQ
877-912-3444 / 952-912-3444 / www.digi.com

DIGI INTERNATIONAL GERMANY
+49-89-540-428-0

DIGI INTERNATIONAL JAPAN
+81-3-5428-0261 / www.digi-intl.co.jp

DIGI INTERNATIONAL SINGAPORE
+65-6213-5380

DIGI INTERNATIONAL CHINA
+86-21-50492199 / www.digi.com.cn

